


DISCLAIMER: The United States Government furnishes this data for informational purposes only and does not warrant, endorse, or guarantee the accuracy, reliability, or availability of the data for any purpose other than that for which it was collected. The user is responsible for the results of any use of the data. The user is advised that the data is not to be used for any purpose other than that for which it was collected. The user is advised that the data is not to be used for any purpose other than that for which it was collected. The user is advised that the data is not to be used for any purpose other than that for which it was collected.

Submitted:	SPSR
Recommended:	MS
Checked By:	MS
Approved:	MS


**CALCASIEU SHIP CHANNEL
BAR SHEET 35
CR_35_BAFX_20170916_CS
16 September 2017**

**Sheet Reference Number
35 of 53**

Revision Number: 3.12-2016011



LEGEND	
--- Federal Navigation Channel	● Cable Area
— Federal Navigation Center Line	□ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
--- Unconfirmed Pipeline/Cable	□ Obstruction Point
— Project Depth Contour	✶ Wrecks-Submerged
3 Fluff Thickness (feet)*	★ Beacon, General
● Shoalest Sounding**	★ Red Navigation Buoy
● -15' and above	★ Green Navigation Buoy
● -15' to -20'	
● -20' to -25'	
● -25' to -32'	
● -32' to -38'	
● -38' to -40'	
● -40' to -42'	
● -42' and below	



NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for page 73650 as of December 2013:
0.0' NAVD88 (2009.55) = 1.3' MLLW = 2.3' MLG or 0.0' MLLW = 1.0' MLG
Distances on the Calcasieu River are shown at 1 mile intervals.
The location of navigation aids are based on and provided by the U.S. Coast Guard and USACE survey crews.
2015 Aerial Photography data source: NAIP
Reference is N.O.A. Navigation Chart No. 11339.
* Difference between high and low frequency elevations where greater than 1.0'.
** Shoalest Sounding per Quarter per Reach.
*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.