U.S. ARMY CORPS OF ENGINEERS 3,478,000 =33°44°37.07° D=9°19'58.59" T=186.19' L=361.55' R=613.91' PACIFICA PARISH, LA. **US Army Corps** of Engineers CITY OF HOUMA District: CEMVN 4" GAS LINE EL. -20 M. L SOUTH LA: ELEC: CO: **TERREBON** SUB. POWER CABLE EL. -20.0 M. L. G. **CURVE 5 DATA** △ =17°34'3.81"/ D=9°23'36.44" T=94.25' L=187.02' R=609.95'/ 661 **CURVE 1 DATA** △ =128°0'27.35" D=57°20'50.95" T=204.88' L=223.21' SOU. BELL TEL. AND TEL. CO. SUB. CABLE EL. -18.0 M. L. G. R=99.91 8" WATER LINE $\overline{\omega}$ JRVE 2 DATA

\[\times = 22^\circ 41'8.56'' \\ D=7^\circ 59'27.46'' \\ T=142.83' \\ R=717.01' \times \quad \ **CURVE 4 DATA** △ =25°57'40.08" D=7°20'19.01" DISPOSAL AREA "A" T=179.97' L=353.76' DISPOSAL AREA 1 HOUMA R=780.74 00+0 INTRACOASTAL A NAVIGATION CANAL VICINITY
BAYOU LECARPE
HN_20_LEC_20190910_CS 2019 BAYOU LEC_201_20_LEC_201 392,000 NOTES: VICINITY MAP Horizontal Coordinate System: z ~~ North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Gage Reading: HOUMA STAFF: 3.38 MLG SMOOTH -10' and above Sea Conditions: Borrow Area Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). --- Federal Navigation Channel Cable Area Datum Relationships for 76320 as of July 2014: 0.0' NAVD88 (2009.55) = 2.42' MLG OB189 Vessel Name: ____ -10' and below Shoalest Sounding** — Federal Navigation Center Line Placement Area Survey Type: Distances on the Houma Nav. Canal are shown at 1 mile intervals. Sounding Frequency***: HIGH As-built Pipeline/Cable Anchorage Area Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews. ∅ Obstruction Point Unconfirmed Pipeline/Cable Red Navigation Buoy Sheet 2010 Aerial Photography data source: NAIP Wrecks-Submerged — Project Depth Contour Reference Reference is N.O.A.A. Navigation Chart No. 11355. Green Navigation Buoy 200 100 300 400 Number ** Shoalest Sounding per Quarter per Reach. **of** 3 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom ri, HERE, Garmin, (c) OpenStreetMa

Revison Number:

4.0-201907022

material. Low frequency accuracies may vary depending on channel conditions and fathometer