



LEGEND

--- Federal Navigation Channel	○ Cable Area	3 Fluff Thickness (feet)*	-10' and above
— Federal Navigation Center Line	□ Placement Area	□ Borrow Area	-10' to -20'
— As-built Pipeline/Cable	□ Anchorage Area	● Shoalest Sounding**	-20' to -30'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	★ Beacon, General	-30' to -40'
— Project Depth Contour	⊙ Wrecks-Submerged	◆ Red Navigation Buoy	-40' to -45'
		◆ Green Navigation Buoy	-45' to -50'
			-50' to -55'
			-55' and below



Gage Reading: 0.3 MLLW @ P.T. (01525) @ 1130
 Sea Conditions: CALM
 Vessel Name: TOBIN
 Survey Type: CONDITION, SB
 Sounding Frequency***: LOW



NOTES:
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum: 0.3 MLLW @ P.T. (01525) @ 1130
 Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-16). Datum Relationships for gage 01525 as of March 2020: 0.0' NAVD83, 2009.55 = -0.53' MLLW = 2.97' MLG
 Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.
 The location of navigation aids are base on and provided by the U.S. Coast Guard.
 2024 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)
 Reference is N.O.A. Navigation Chart No. 11361.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

US Army Corps of Engineers District: CEMVN

DISCLAIMER: The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that the data are not to be used for any purpose other than that for which they were originally prepared, and that the Government assumes no liability whatsoever to any person by reason of any use of these data, in whole or in part, for any purpose other than that for which they were originally prepared. The recipient agrees not to represent these data to anyone as other than Government provided data. The recipient may not transfer these data to others without also transferring the disclaimer. The information depicted on this map represents the results of a survey conducted on or about the date indicated on the map. It is not to be used for any purpose other than that for which it was prepared.

DISTRIBUTION STATEMENT: This data represents the results of data collection processing for a specific US Army Corps of Engineers activity and indicates the general operating conditions. As such, the data are not to be used for any purpose other than that for which they were originally prepared, and that the Government assumes no liability whatsoever to any person by reason of any use of these data, in whole or in part, for any purpose other than that for which they were originally prepared. The recipient agrees not to represent these data to anyone as other than Government provided data. The recipient may not transfer these data to others without also transferring the disclaimer. The information depicted on this map represents the results of a survey conducted on or about the date indicated on the map. It is not to be used for any purpose other than that for which it was prepared.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT

Submitted:	JUC & RCC
Recommended:	TSS
Approved:	MSK

Chief, Survey Section
 Chief, Waterways Maintenance Section

MISSISSIPPI RIVER - B.R. TO GULF PILOTTOWN ANCHORAGE
SW_00_PTAX_20250310_CS
 10 March 2025

Sheet Reference Number
 4 of 13

Revision Number: 5.23.12.3-3.12.3