


**LEGEND**

--- Federal Navigation Channel	--- Cable Area	□ Borrow Area	■ -12' and above
— Federal Navigation Center Line	■ Placement Area	● Shoalest Sounding**	■ -12' to -15'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -15' to -18'
--- Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	■ -18' to -20'
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	■ -20' and below
			■ Fluff Thickness*



Gage Reading: EUGINE ISLAND: 2.68 AVG.  
 Sea Conditions: 2-4 FT  
 Vessel Name: MV VALENTOUR  
 Survey Type: CONDITION  
 Sounding Frequency\*\*\*: LOW

Feet  
 0 800 1,600 2,400 3,200

**NOTES:**  
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.  
 Vertical Datum: Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for the gage 88600 as of August 2013: 0.07 NAVD83 = 0.01 MLLW = 1.5' MLG  
 Distances on the Atchafalaya River are shown at 1 mile intervals.  
 The location of navigation aids are based on and provided by the U.S. Coast Guard.  
 2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).  
 Reference is N.O.A.A. Navigation Chart No. 11354.  
 \* Difference between high and low frequency elevations where greater than 1.0'.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetry settings.

**DISTRICT OFFICE:** The United States Government is authorized to reproduce and distribute reprints for government purposes not withstanding any copyright notation that may appear hereon. The views and opinions of the authors are those of the authors and do not necessarily represent those of the U.S. Army Corps of Engineers. The use of trade names or product names is for identification only and does not constitute an endorsement or approval of the quality or value of the product named. The use of trade names or product names is for identification only and does not constitute an endorsement or approval of the quality or value of the product named. The use of trade names or product names is for identification only and does not constitute an endorsement or approval of the quality or value of the product named.

Submitted By:	RYLAND/DAMS
Reviewed By:	BD
Checked By:	AO

**ATCHAFALAYA RIVER  
 BAR CHANNEL  
 AR\_01\_BAR\_20190625\_CS  
 25 June 2019**

**Sheet Reference Number  
 1 of 16**