



# Sheet Reference Number 3 of 16

- Compass rose showing North (N), South (S), East (E), and West (W).

Scale bar labeled "Feet" with markings at 0, 800, 1,600, 2,400, and 3,200.

3,258,000

**NOTES:**

Horizontal Coordinate System:  
Horizontal Position Datum of 1989 (NAD83), projected to the State Plane  
Coordinate System (SPCS), Louisiana South Zone. Distances units in U.S. Survey Feet.

Vertical Datum:  
Distances are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
Datum: Relationship for the page #8800 as of August 1986:  
0.0 NAVD08 + 0.6 MLLW = 1.5 MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard.

1998 Aerial Photography source: PAR, LLC (1998 DOQQ imagery in green).

Reference is N.O.A. Navigation Chart No. 11334.

\*\* Difference between high and low frequency elevations where greater than 1'.

\*\* Shoaled Soundings per Quarter per Reach.

\*\* High frequency (20 kHz) survey data represents the first signal return at 20 kHz soundings and is used to determine the location of the "T" buoy. If present, Low frequency (20 kHz) survey data normally penetrates through this "T" buoy layer to depth conditions of consolidated material. Low frequency accuracies may vary depending on channel conditions and bathymetric settings.