



**LEGEND**

--- Federal Navigation Channel	--- Cable Area	□ Borrow Area	■ -15' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	■ -15' to -20'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -20' and below
--- Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	3 Fluff Thickness*
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	

This data was collected in cooperation with the Port of Morgan City. The Port of Morgan City is not responsible for errors or omissions contained in this data set.

Gage Reading: EUGENE ISLAND: 2.011.3 MLG  
 Sea Conditions: CALM  
 Vessel Name: MV BURRWOOD  
 Survey Type: MC RHEOTUNE  
 Sounding Frequency: N/A

Vertical Datum:  
 Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
 Datum Relationships for the gage 88600 as of August 2013:  
 0.0' NAVD83 = 0.0' MLLW = 1.5' MLG

Distances on the Atchafalaya River are shown on a 1 mile interval.

The location of navigation aids are based on and provided by the U.S. Coast Guard.  
 2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).  
 Reference is N.O.A.A. Navigation Chart No. 11354.

\* Difference between high and low frequency elevations where greater than 1.0'.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetry settings.

**NOTES:**  
 Horizontal Coordinate System:  
 North American Datum of 1983 (NAD83), projected to the State Plane  
 Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
 Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
 Datum Relationships for the gage 88600 as of August 2013:  
 0.0' NAVD83 = 0.0' MLLW = 1.5' MLG

Distances on the Atchafalaya River are shown on a 1 mile interval.

The location of navigation aids are based on and provided by the U.S. Coast Guard.  
 2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).  
 Reference is N.O.A.A. Navigation Chart No. 11354.

\* Difference between high and low frequency elevations where greater than 1.0'.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetry settings.

U.S. ARMY CORPS OF ENGINEERS  
 NEW ORLEANS DISTRICT

Author:	Engineer:
Checked:	DR/LA
Reviewed:	Planner:
Approved:	BD
Checked:	AO

**ATCHAFALAYA RIVER**  
**BAR CHANNEL**  
**AR\_03\_DEN\_20161121**  
**21 November 2016**

**Sheet Reference Number**  
**3 of 16**

Revision Number:  
 3.8.2016.002

**DISCLAIMER:** The United States Government neither warrants nor makes any representation, express or implied, regarding the accuracy, reliability, completeness, or timeliness of the information provided herein. The user shall be responsible for the accuracy, reliability, completeness, or timeliness of the information provided. The user shall be responsible for the accuracy, reliability, completeness, or timeliness of the information provided. The user shall be responsible for the accuracy, reliability, completeness, or timeliness of the information provided.

**US Army Corps of Engineers District: CEMVN**