








LEGEND							
---	Federal Navigation Channel		Cable Area		Borrow Area		-12' and above
—	Federal Navigation Center Line		Placement Area		Shoalest Sounding**		-12' to -15'
—	As-built Pipeline/Cable		Anchorage Area		Beacon, General		-15' to -18'
.....	Unconfirmed Pipeline/Cable		Obstruction Point		Red Navigation Buoy		-18' to -20'
—	Project Depth Contour		Wrecks-Submerged		Green Navigation Buoy		-20' and below
						3	Fluff Thickness*



NOTES: 330,000

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana State Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).
Datum Relationships for the page 88000 are as of August 2013:
0.7 NAVD83 = 0.6 MLG, MLG = 1.5 MLLW

Distances on the Atchafalaya River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard.

2019 Aerial Photographic data source: PAR, LLC, (1998 DOQQ imagery in green).

Reference is N.O.A. Navigation Chart No. 11354.

*** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff". High frequency (200 kHz) survey data normally penetrates through this "fluff" layer to detect elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetric settings.