



LEGEND

--- Federal Navigation Channel	--- Cable Area	□ Borrow Area	■ -15' and above
— Federal Navigation Center Line	■ Placement Area	● Shoalest Sounding**	■ -15' to -20'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -20' and below
--- Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for the gauge 88600 as of August 2013:
0.0' NAVD83 = 0.6' MLLW = 1.5' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.
The location of navigation aids are based on and provided by the U.S. Coast Guard.
2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).
Reference is N.O.A.A. Navigation Chart No. 11354.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return of a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetric settings.

Gage Reading: EUGENE ISLAND: 2.0 MLG AVG
Sea Conditions: CHOPPY
Vessel Name: M/V BURRWOOD
Survey Type: CONDITION
Sounding Frequency***: LOW

Feet
0 800 1,600 2,400 3,200 4,000

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for the gauge 88600 as of August 2013:
0.0' NAVD83 = 0.6' MLLW = 1.5' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.
The location of navigation aids are based on and provided by the U.S. Coast Guard.
2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).
Reference is N.O.A.A. Navigation Chart No. 11354.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return of a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetric settings.

DISCLAIMER: The data presented in this report is the property of the U.S. Army Corps of Engineers and is provided for informational purposes only. It is not intended for use in any other context. The user assumes all liability for any use of the data other than that intended by the U.S. Army Corps of Engineers. The U.S. Army Corps of Engineers does not warrant the accuracy or completeness of the data. The user shall verify the accuracy and completeness of the data before using it for any purpose. The U.S. Army Corps of Engineers is not responsible for any errors or omissions in this report. The user shall be responsible for any errors or omissions in this report. The U.S. Army Corps of Engineers is not responsible for any errors or omissions in this report. The user shall be responsible for any errors or omissions in this report.

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT

Author:	RYLAND/DAMS
Revised:	By AC
Checked:	Checked By AN
Approved:	Checked By AN

**ATCHAFALAYA RIVER
UPPER BAY CHANNEL
AR_06_BAY_20160114
14 January 2016**

**Sheet
Reference
Number
6 of 16**

Revision Number:
3.8.20160202