



LEGEND

--- Federal Navigation Channel	--- Cable Area	□ Borrow Area	■ -12' and above
— Federal Navigation Center Line	■ Placement Area	● Shoalest Sounding**	■ -12' to -15'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -15' to -18'
--- Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	■ -18' to -20'
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	■ -20' and below
			3 Fluff Thickness*

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
SOUNDINGS are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).
Datum Relationships for the gauge 85600 as of August 2013:
0.0' NAVD83 = 0.6' MLW = 1.5' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard.

2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).

Reference is N.O.A.A. Navigation Chart No. 11354.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetry settings.

Gage Reading: EUGINE ISLAND: 3.0 MLG
Sea Conditions: LIGHT
Vessel Name: OB-189
Survey Type: CONDITION
Sounding Frequency***: LOW

Feet
0 800 1,600 2,400 3,200 4,000

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
SOUNDINGS are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).
Datum Relationships for the gauge 85600 as of August 2013:
0.0' NAVD83 = 0.6' MLW = 1.5' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard.

2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).

Reference is N.O.A.A. Navigation Chart No. 11354.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetry settings.

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT

Project: ATCHAFALAYA RIVER UPPER BAY CHANNEL
AR_06_BAY_20180405_CS
05 April 2018

Sheet Reference Number: 6 of 16

Revision Number: 1.12-20180411

Author: [Blank]
Checked By: [Blank]
Reviewed By: [Blank]

Drawn By: OSJH
Plotted By: [Blank]
ID: [Blank]
Checked By: [Blank]
AO: [Blank]

Disclaimer: The data shown on this map was derived from the most current available data and is subject to change without notice. The user assumes all responsibility for the use of this information. The user assumes all responsibility for the use of this information. The user assumes all responsibility for the use of this information.