



LEGEND

--- Federal Navigation Channel	--- Cable Area	□ Borrow Area	■ -12' and above
— Federal Navigation Center Line	■ Placement Area	● Shoalest Sounding**	■ -12' to -15'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -15' to -18'
--- Unconfirmed Pipeline/Cable	⊗ Obstruction Point	★ Red Navigation Buoy	■ -18' to -20'
— Project Depth Contour	⚓ Wrecks-Submerged	★ Green Navigation Buoy	■ -20' and below
			3 Fluff Thickness*

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for the gauge 89500 as of August 2013:
0.0' NAVD83 = 0.6' MLW = 1.5' MLG

Distances on the Atchafalaya aids are shown at 1 mile intervals.
The location of navigation aids are based on and provided by the U.S. Coast Guard.
2019 Aerial Photography data source: PAR, LLC (1998 DOQQ imagery in green).
Reference is N.O.A. Navigation Chart No. 11354.

*** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymeter settings.

Gage Reading: EUGINE ISLAND: 2.74 MLG
Sea Conditions: CALM/CHOPPY
Vessel Name: OB-167
Survey Type: CONDITION
Sounding Frequency***: LO

Feet
0 800 1,600 2,400 3,200 4,000

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for the gauge 89500 as of August 2013:
0.0' NAVD83 = 0.6' MLW = 1.5' MLG

Distances on the Atchafalaya aids are shown at 1 mile intervals.
The location of navigation aids are based on and provided by the U.S. Coast Guard.
2019 Aerial Photography data source: PAR, LLC (1998 DOQQ imagery in green).
Reference is N.O.A. Navigation Chart No. 11354.

*** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymeter settings.

US Army Corps of Engineers District: CEMVN

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT

Submitted By: DM/A	Checked By: KAC/JH
Reviewed By: BD	Approved By: KAC/JH
Chief, Survey Section	Chief, Waterways Maintenance Section

ATCHFALAYA RIVER UPPER BAY CHANNEL AR_06_BAY_20220915_CS 15 September 2022

Sheet Reference Number 6 of 16

Revision Number: 4.2-20200420