



LEGEND

--- Federal Navigation Channel	--- Cable Area	□ Borrow Area	■ -12' and above
— Federal Navigation Center Line	■ Placement Area	● Shoalest Sounding**	■ -12' to -15'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -15' to -18'
--- Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	■ -18' to -20'
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	■ -20' and below
			3 Fluff Thickness*

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 03820 as of August 2013:
0.7' MLLW = 0.0' NAVD86 = 2.9' MLG

AVOCA ISLAND: 3.58 MLG
Sea Conditions: CALM
Vessel Name: OB-189
Survey Type: CONDITION
Sounding Frequency**: HIGH

Distances on the Atchafalaya River are shown at 1 mile intervals.
The location of navigation aids are based on and provided by the U.S. Coast Guard.
2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).
Reference is N.O.A.A. Navigation Chart No. 11354.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as 'fluff', if present. Low frequency (20 kHz) survey data normally penetrates through this 'fluff' layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymeter settings.

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 03820 as of August 2013:
0.7' MLLW = 0.0' NAVD86 = 2.9' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.
The location of navigation aids are based on and provided by the U.S. Coast Guard.
2013 Aerial Photography data source: GEOCLIP, Atlantic Group, LLC. (1998 DOQQ imagery in green).
Reference is N.O.A.A. Navigation Chart No. 11354.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as 'fluff', if present. Low frequency (20 kHz) survey data normally penetrates through this 'fluff' layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymeter settings.

DISCLAIMER: The United States Government is authorized to reproduce and distribute reprints for government purposes not withstanding any copyright notation that may appear hereon. The United States Government does not warrant the accuracy or completeness of the information furnished herein. The user assumes all responsibility for the use of the information furnished herein. The user shall indemnify and hold the United States Government harmless from all claims, damages, and expenses, including reasonable attorneys' fees, arising out of or from the use of the information furnished herein, whether or not such claims, damages, and expenses are caused in whole or in part by the negligence of the United States Government. The user shall also indemnify and hold the United States Government harmless from all claims, damages, and expenses, including reasonable attorneys' fees, arising out of or from the use of the information furnished herein, whether or not such claims, damages, and expenses are caused in whole or in part by the negligence of the user.

Customer:	RYLAND/DAMS
Prepared By:	BD
Checked By:	AO

**ATCHAFALAYA RIVER
CREWBOAT CUT CHANNEL
AR_07_CEC_20180208_CS
08 February 2018**

**Sheet Reference Number
7 of 16**