U.S. ARMY CORPS OF ENGINEERS US Army Corps of Engineers District: CEMVN Constant of Consta NOTES: Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).
Datum Relationships for gage 03820 as of August 2013:
-0.7' MLLW = 0.0' NAVD88 = 2.9' MLG --- Federal Navigation Channel Shoalest Sounding** CONDITION Distances on the Atchafalaya River are shown at 1 mile intervals. -15' to -18' Sounding Frequency***: LOW The location of navigation aids are base on and provided by the U.S. Coast Guard. As-built Pipeline/Cable -18' to -20' 2019 Aerial Photography data source: PAR, LLC. (1998 DOQQ imagery in green). Unconfirmed Pipeline/Cable Reference is N.O.A.A. Navigation Chart No. 11354. -20' and below Reference ** Shoalest Sounding per Quarter per Reach. Project Depth Contour Wrecks-Submerged Number *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) **Green Navigation Buoy** Thickness* 2,400 0 10 20 Miles survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer Esri, HERE, Garmin, (c) OpenStreetMap contributors, and the GIS user Revison Number: 4.1-20191105