



**LEGEND**

--- Federal Navigation Channel	--- Cable Area	□ Borrow Area	■ -12' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	■ -12' to -15'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -15' to -18'
--- Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	■ -18' to -20'
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	■ -20' and below
			3 Fluff Thickness*

Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
Datum Relationships for gauge 0350 as of August 2020:  
0.0' NAVD83 = 3.07' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.  
The location of navigation aids are based on and provided by the U.S. Coast Guard.  
2019 Aerial Photography data source: PRR, LLC (1998 DOQQ imagery in green).  
Reference is N.O.A.A. Navigation Chart No. 11354.

\*\* Shoalest Sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymeter settings.

Gage Reading: DM 12: 3.84 MLG AVG.  
Sea Conditions: CALM  
Vessel Name: MV VALENTOUR  
Survey Type: CONDITION  
Sounding Frequency\*\*\*: HIGH

Scale: 0 800 1,600 2,400 3,200 4,000 Feet

**NOTES:**

Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
Datum Relationships for gauge 0350 as of August 2020:  
0.0' NAVD83 = 3.07' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.  
The location of navigation aids are based on and provided by the U.S. Coast Guard.  
2019 Aerial Photography data source: PRR, LLC (1998 DOQQ imagery in green).  
Reference is N.O.A.A. Navigation Chart No. 11354.

\*\* Shoalest Sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymeter settings.

**DISCLAIMER:** The data presented in this map is the property of the U.S. Army Corps of Engineers and is provided for informational purposes only. It is not intended to be used for any other purpose. The user assumes all liability for any use of the data other than that intended. The U.S. Army Corps of Engineers does not warrant the accuracy or completeness of the data. The U.S. Army Corps of Engineers is not responsible for any errors or omissions in the data. The U.S. Army Corps of Engineers is not responsible for any damage or loss resulting from the use of the data. The U.S. Army Corps of Engineers is not responsible for any claims, damages, or liabilities arising from the use of the data. The U.S. Army Corps of Engineers is not responsible for any claims, damages, or liabilities arising from the use of the data.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT	
Author:	CHAMPNEADAMS
Illustration:	CHAMPNEADAMS
Checked By:	ACAH
Approved:	ACAH

**ATCHAFALAYA RIVER  
CREWBOAT CUT CHANNEL  
AR\_07\_CBC\_20240123\_CS  
23 January 2024**

**Sheet Reference Number  
7 of 16**