







LEGEND							
---	Federal Navigation Channel		Cable Area		Borrow Area		-12' and above
—	Federal Navigation Center Line		Placement Area		Shoalest Sounding**		-12' to -15'
—	As-built Pipeline/Cable		Anchorage Area		Beacon, General		-15' to -18'
.....	Unconfirmed Pipeline/Cable		Obstruction Point		Red Navigation Buoy		-18' to -20'
—	Project Depth Contour		Wrecks-Submerged		Green Navigation Buoy		-20' and below
							Fluff Thickness*



NOTES: **380,000**

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distances units in U.S. Survey Feet.

Vertical Datum: Mean Sea Level (MSL)

Soundings are shown in feet and indicate depths below Mean Low Gull Datum (MLG).
Date of Soundings for page 03820 as of August 2020:
0.0' NAVD83 = 3.07' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard.

2010 Aerial Photograph data source: PAR, LLC, 1998 DOQQ imagery in green.

Reference is to N.O.A. Navigation Chart No. 11354.

* * * Shoalest Sounding per Quarter per Reach.

*** High frequency (20 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bottom sediment types.