



LEGEND

--- Federal Navigation Channel

— Federal Navigation Center Line

— As-built Pipeline/Cable

..... Unconfirmed Pipeline/Cable

— Project Depth Contour

○ Cable Area

□ Anchorage Area

⊗ Obstruction Point

✈ Wrecks-Submerged

□ Borrow Area

● Shoalest Sounding**

★ Beacon, General

◆ Red Navigation Buoy

◆ Green Navigation Buoy

■ -12' and above

■ -12' to -15'

■ -15' to -18'

■ -18' to -20'

■ -20' and below

3 Fluff Thickness*

Gage Reading: AMELIA: 3.58 MLG

Sea Conditions: CALM

Vessel Name: OB-169

Survey Type: CONDITION

Sounding Frequency***: 200

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 52800 as of August 2013:
0.0' NAVD88 = 1.7' MLG

Distances on the Atchafalaya River are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2019 Aerial Photography data source: PAR, LLC

Reference is N.O.A.A. Navigation Chart No. 11354.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT			
Submitted:	Surveyed By: PMLT	Plotted By: BD	Checked By: AOJH
Recommended:	Chief, Survey Section		Chief, Waterways Maintenance Section
Approved:			

ATCHAFALAYA RIVER

BAYOU BLACK

AR_16_BLK_20250715_CS

15 July 2025

Sheet

Reference

Number

16 of 16

Revision Number:
5.25.04.03-5.25.04.03

DISCLAIMER

Access Conditions: The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that the data are not to be used for any purpose other than that for which they were originally collected, processed, or disseminated. The user is responsible for the results of any application of the data for other than its intended purpose.

Data Contents: Hydrographic survey data is subject to change and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings. This data is intended for U.S. Army Corps of Engineers internal use. Prudent mariners should not rely solely upon it.

**US Army Corps
of Engineers**

District: CEMVN