U.S. ARMY CORPS OF ENGINEERS US Army Corps of Engineers District: CEMVN ATCHAFALAYA RIVER
BERWICK LOCK FOREBAY
AS_00_BLF_20251029_CS
29 October 2025 NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **VICINITY MAP LEGEND** Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).
Datum Relationships for Lower Atchafalaya River at Morgan City (03780) as of 2025:
0.0' NAVD88 (2009.55) = 2.19' MLG MORGAN CITY: 3.10 MLG AVG. ____ -6' and above Gage Reading: CALM --- Federal Navigation Channel Cable Area Borrow Area Sea Conditions: -6 to -8 DUCARPE -8 to -10 Shoalest Sounding** — Federal Navigation Center Line Placement Area The location of navigation aids are base on and provided by the U.S. Coast Guard. Survey Type: -10 to -12 Sounding Frequency***: 200 As-built Pipeline/Cable [__] Anchorage Area Beacon, General -12' to -15' 2021 Aerial Photography data source: NAIP. -15' to -18' Reference is N.O.A.A. Navigation Chart No. 11355. ∅ Obstruction Point Unconfirmed Pipeline/Cable Red Navigation Buoy -18' to -20' Sheet ** Shoalest Sounding per Quarter per Reach. — Project Depth Contour Wrecks-Submerged -20' and below Reference *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) Green Navigation Buoy 200 300 Number survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer of 1

Revison Number: 5.25.08.04