



**LEGEND**

--- Federal Navigation Channel	○ Cable Area	□ Borrow Area	■ -12' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	□ -12' and below
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	
— Project Depth Contour	✈ Wrecks-Submerged	◆ Green Navigation Buoy	

Gage Reading: CP:7.7 MC:5.4 USED: 6.0 MLG  
 Sea Conditions: CALM  
 Vessel Name: OB-189  
 Survey Type: CONDITION  
 Sounding Frequency\*\*\*: HIGH

Vertical Datum:  
 Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
 The location of navigation aids are base on and provided by the U.S. Coast Guard.  
 Reference is N.O.A. Navigation Chart No. 11355.  
 \*\*\* Shoalest Sounding per Quarter per Reach.

\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

**NOTES:**

Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
The location of navigation aids are base on and provided by the U.S. Coast Guard.  
Reference is N.O.A. Navigation Chart No. 11355.

\*\*\* Shoalest Sounding per Quarter per Reach.  
\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



**Access/Consent:** The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that they are for official use only and that they are not to be distributed, copied, or used for any other purpose without the express written consent of the Government. The user is responsible for the accuracy, completeness, and reliability of the data for other than its intended purpose. The application of the data for other than its intended purpose is at the user's risk. The user is responsible for the accuracy, completeness, and reliability of the data for other than its intended purpose. The application of the data for other than its intended purpose is at the user's risk. The user is responsible for the accuracy, completeness, and reliability of the data for other than its intended purpose. The application of the data for other than its intended purpose is at the user's risk.

U.S. ARMY CORPS OF ENGINEERS  
NEW ORLEANS DISTRICT

Submitted:	Surveyed By: JH-SR
Recommended: Chief Survey Section	Plotted By: BTD
Approved: Chief Waterways Maintenance Section	Checked By: TC

**ATCHAFALAYA RIVER  
STOUTS PASS  
AS\_08\_STP\_20160308  
08 March 2016**

**Sheet  
Reference  
Number  
8 of 66**