U.S. ARMY CORPS OF ENGINEERS 3,316,000 3,319,000 458,000 US Army Corps of Engineers District: CEMVN ATCHAFALAYA RIVER
STOUTS PASS
AS_08_STP_20230613_AE
13 June 2023 455,000 452,000 3,310,000 449,000 3,313,000 446,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. <u>LEGEND</u> Gage Reading: VRS RTN: 3.65 MLG AVG. CALM ____ -10' and above --- Federal Navigation Channel Cable Area Borrow Area Sea Conditions: Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). OB-167 Vessel Name: -10 to -12 The location of navigation aids are base on and provided by the U.S. Coast Guard. — Federal Navigation Center Line Placement Area Shoalest Sounding** Survey Type: CONDITION -12' to -15' 2017 Aerial Photography data source: NAIP. 1998 DOQQ imagery shown in green from USGS. Sounding Frequency***: HI As-built Pipeline/Cable -15' to -18' [__] Anchorage Area Beacon, General -18' to -20' ∅ Obstruction Point Reference is N.O.A.A. Navigation Chart No. 11355. Unconfirmed Pipeline/Cable Red Navigation Buoy -20' and below Sheet ** Shoalest Sounding per Quarter per Reach. Wrecks-Submerged — Project Depth Contour Reference Green Navigation Buoy *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) 1,000 1,500 2,000 Number survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer 8 **of** 66 Revison Number: 4.2-20200420