


**DISTRIBUTION LIABILITY:** The data represents the results of data collection/processing for a specific US Army Corps of Engineers project. It is only valid for its intended use, content, time and accuracy specifications. The user is responsible for the results for any other purpose. The user is responsible for the results for any other purpose. The user is responsible for the results for any other purpose.

|              |                   |
|--------------|-------------------|
| Submitted:   | Surveyed By: SPPM |
| Recommended: | Plotted By: BD    |
| Approved:    | Checked By: AC    |


**BARATARIA WATERWAY LOWER CHANNEL**  
 BW\_18\_LWR\_20171108\_CS  
 08 November 2017

**Sheet Reference Number**  
 18 of 20

Revision Number: 3.12-20160811



| LEGEND                           |                     |                         |                  |
|----------------------------------|---------------------|-------------------------|------------------|
| --- Federal Navigation Channel   | ○ Cable Area        | □ Borrow Area           | ■ -8' and above  |
| — Federal Navigation Center Line | □ Placement Area    | ● Shoalest Sounding**   | ■ -8' to -12'    |
| — As-built Pipeline/Cable        | □ Anchorage Area    | ★ Beacon, General       | ■ -12' to -15'   |
| ..... Unconfirmed Pipeline/Cable | ⊗ Obstruction Point | ◆ Red Navigation Buoy   | ■ -15' and below |
| — Project Depth Contour          | ⚓ Wrecks-Submerged  | ◆ Green Navigation Buoy |                  |



**NOTES:**  
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.  
 Vertical Datum: Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
 Distances on the Barataria Waterway are shown at 1 mile intervals.  
 The location of navigation aids are based on and provided by the U.S. Coast Guard and USACE survey crews.  
 2010 Aerial Photography data source: NAIP  
 Reference is N.O.A.A. Navigation Chart No. 11365.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.