U.S. ARMY CORPS OF ENGINEERS 2,671,000 2,668,000 US Army Corps of Engineers **District: CEMVN DISPOSAL AREA 4** Bayou D'Inde Junction | Buoy BD LCASIEU SHIP CHANNEL
UPPER SHEET 3
PR_20201012_CS_POSTS1 2020 2,668,000 626,000 2,665,000 629,000 NOTES: Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane VICINITY MAP 12 Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Vertical Datum: -16' and above VRS: 2.5 MLG AVG Gage Reading: Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). 3 Fluff Thickness (feet)* Datum Relationships for gage 73550 as of December 2013: 0.0' NAVD88 (OPUS 2010) = 0.6' MLLW = 1.6' MLG or 0.0' MLLW = 1.0' MLG ROUGH NEAR LAKES -16' to -21' Cable Area Sea Conditions: --- Federal Navigation Channel M/V OB-169 -21' to -26' Vessel Name: — Federal Navigation Center Line Placement Area Shoalest Sounding** Distances on the Calcasieu River are shown at 1 mile intervals. CONDITION -26' to -33' Esri, HERE Garmin (c) OpenSt the GIS user community Sounding Frequency***: LOW **Upper Channel** The location of navigation aids are base on and provided by the U.S. Coast Guard As-built Pipeline/Cable Anchorage Area -33' to -39' Beacon, General and USACE survey crews. -39' to -41' ∅ Obstruction Point ---- Unconfirmed Pipeline/Cable 2015 Aerial Photography data source: NAIP Red Navigation Buoy Sheet -41' to -43' Reference is N.O.A.A. Navigation Chart No. 11339. — Project Depth Contour Wrecks-Submerged Reference -43' and below Green Navigation Buoy 400 1,200 * Difference between high and low frequency elevations where greater than 1.0'. Number 3 **of** 53 ** Shoalest Sounding per Quarter per Reach. *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Revison Number: material. Low frequency accuracies may vary depending on channel conditions and fathometer 4.1-20191105