



LEGEND		
--- Federal Navigation Channel	○ Cable Area	3 Fluff Thickness (feet)*
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**
— As-built Pipeline/Cable	⊗ Anchorage Area	★ Beacon, General
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy
— Project Depth Contour	⊗ Wrecks-Submerged	◆ Green Navigation Buoy

Gage Reading: DM 119 VRN: 1.75 MLLW AVG.
 Sea Conditions: CALM
 Vessel Name: M/V TECHE
 Survey Type: CONDITION
 Sounding Frequency***: LOW

NOTES:
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73550 as of December 2013: 0.0' NAVD88 (OPUS 2010) = 0.6' MLLW = 1.6' MLG or 0.0' MLLW = 1.0' MLG
 Distances on the Calcasieu River are shown at 1 mile intervals.
 The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.
 2022 Aerial Photography data source: PAR LLC
 Reference is N.O.A. Navigation Chart No. 11339.
 * Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



DISTRIBUTION LIABILITY: The data represents the results of data collection/processing for a specific US Army Corps of Engineers project. It is only valid for its intended use, content, time and accuracy specifications. The user is responsible for the results of any use under no liability whatsoever to any person by reason of any use of the data. The user agrees to hold the US Army Corps of Engineers harmless from any and all claims, damages, losses, and expenses, including reasonable attorneys' fees, that may be incurred by the user or any third party as a result of the use of the data for any purpose other than that for which it was provided. The user agrees to indemnify and hold the US Army Corps of Engineers harmless from any and all claims, damages, losses, and expenses, including reasonable attorneys' fees, that may be incurred by the user or any third party as a result of the use of the data for any purpose other than that for which it was provided. The user agrees to indemnify and hold the US Army Corps of Engineers harmless from any and all claims, damages, losses, and expenses, including reasonable attorneys' fees, that may be incurred by the user or any third party as a result of the use of the data for any purpose other than that for which it was provided.

Submitted:	Surveyed By: SPJS
Recommended:	Plotted By: BD
Approved:	Checked By: ADJH

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT

**CALCASIEU SHIP CHANNEL
 UPPER SHEET 3
 CR_03_UPR_20241009_CS
 09 October 2024**

**Sheet Reference Number
 3 of 53**