


DISCLAIMER
 The information depicted on this map represents the results of a survey conducted for the purpose of determining the general condition of the waterway. The user is responsible for the accuracy, completeness, and timeliness of the data used in the survey. The user is responsible for the accuracy, completeness, and timeliness of the data used in the survey. The user is responsible for the accuracy, completeness, and timeliness of the data used in the survey.


Submitted:	Reviewed By:	Checked By:
	SURJH	AC
Recommended:	Plotted By:	
Chief, Survey Section	BD	
Approved:		
Chief, Waterways Maintenance Section		

**CALCASIEU SHIP CHANNEL
 UPPER SHEET 7
 CR_07_UPR_20170516_CS
 16 May 2017**

**Sheet Reference Number
 7 of 53**



LEGEND	
--- Federal Navigation Channel	○ Cable Area
— Federal Navigation Center Line	□ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point
— Project Depth Contour	✳ Wrecks-Submerged
3 Fluff Thickness (feet)*	★ Beacon, General
● Shoalest Sounding**	♦ Red Navigation Buoy
● Green Navigation Buoy	



Gage Reading:
 Sea Conditions:
 Vessel Name:
 Survey Type:
 Sounding Frequency***: LOW

RANGE E: 2.9 MLG
 CALM
 M/V TECHE
 CONDITION

0 400 800 1,200 1,600
 Feet

NOTES:
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum: Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 73575 as of December 2013: 0.0' NAVD83 (OPUS 2013) = 0.8' MLLW = 1.8' MLG or 0.0' MLLW = 1.0' MLG
 Distances on the Calcasieu River are shown at 1 mile intervals.
 The location of navigation aids are based on and provided by the U.S. Coast Guard and USACE survey crews.
 2015 Aerial Photography data source: NAIP
 Reference is N.O.A.A. Navigation Chart No. 11339.
 * Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.