

Distribution Liability: The data represents the results of data collection/processing for a specific US Army Corps of Engineers project. It is only valid for its intended use, content, time and accuracy specifications. The user is responsible for the results. The user must verify the accuracy of the data for their intended purpose.

Data Constants: Hydrographic survey data is subject to change rapidly due to several factors including, but not limited to, changing hydrographic conditions, changes in the datum, and changes in the hydrographic conditions which develop after the date of the survey. The user is responsible for the results of the data. The user must verify the accuracy of the data for their intended purpose.


| | |
|--------------|--------------------|
| Submitted: | Surveyed By: SP-JS |
| Recommended: | Plotted By: JH |
| Approved: | Checked By: JH |

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT


**CALCASIEU SHIP CHANNEL
UPPER SHEET 8
CR_08_UPR_20241008_CS
08 October 2024**

**Sheet Reference Number
8 of 53**

Revision Number:
4-2-2024(04/24)



| LEGEND | | |
|----------------------------------|---------------------|---------------------------|
| --- Federal Navigation Channel | ○ Cable Area | 3 Fluff Thickness (feet)* |
| — Federal Navigation Center Line | □ Placement Area | ● Shoalest Sounding** |
| — As-built Pipeline/Cable | ⊗ Anchorage Area | ★ Beacon, General |
| Unconfirmed Pipeline/Cable | ⊗ Obstruction Point | ◆ Red Navigation Buoy |
| — Project Depth Contour | ⊗ Wrecks-Submerged | ◆ Green Navigation Buoy |



NOTES:
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73575 as of December 2013: 0.0' NAVD83 (OPUS 2013) = 0.8' MLLW = 1.8' MLG or 0.0' MLLW = 1.0' MLG
 Distances on the Calcasieu River are shown at 1 mile intervals.
 The location of navigation aids are based on and provided by the U.S. Coast Guard and USACE survey crews.
 2022 Aerial Photography data source: PAR LLC
 Reference is N.O.A. Navigation Chart No. 11339.
 * Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.