U.S. ARMY CORPS OF ENGINEERS 578,000 575,000 US Army Corps of Engineers District: CEMVN LL=45.7 MLLW 44. CALCASIEU SEP CHANNEL LL=46.7 MLLW LL=45.7 MLLW DISPOSAL AREA 15 LOWER SHEET 11

11_LWR_20240808_BD 581,000 578,000 575,000 CALCASIEU NOTES: Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane VICINITY MAP Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** -16' and above DM 86 VRN: 1.3 MLLW AVG. Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73595 as of December 2013:

0.0' NAVD88 (OPUS 2013) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG Gage Reading: 3 Fluff Thickness (feet)* CALM -16' to -21' Sea Conditions: --- Federal Navigation Channel Cable Area M/V TECHE -21' to -26' Vessel Name: 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 — Federal Navigation Center Line Placement Area Shoalest Sounding** Distances on the Calcasieu River are shown at 1 mile intervals. CONDITION Survey Type: -26' to -33' Esri, HERE Garmin (c) OpenStr the GIS user Community Sounding Frequency***: LOW The location of navigation aids are base on and provided by the U.S. Coast Guard **Upper Channel** As-built Pipeline/Cable Anchorage Area Beacon, General -33' to -39' and USACE survey crews. -39' to -41' ∅ Obstruction Point Unconfirmed Pipeline/Cable 2022 Aerial Photography data source: PAR LLC 40 41 42 43 44 45 46 47 48 49 Red Navigation Buoy Sheet -41' to -43' Reference is N.O.A.A. Navigation Chart No. 11339. — Project Depth Contour Wrecks-Submerged Reference -43' and below Green Navigation Buoy 1,200 400 * Difference between high and low frequency elevations where greater than 1.0'. Number 11 **of** 53 ** Shoalest Sounding per Quarter per Reach. *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom

Revison Number: 4.2-20200420

material. Low frequency accuracies may vary depending on channel conditions and fathometer