U.S. ARMY CORPS OF ENGINEERS 566,000 US Army Corps of Engineers **District: CEMVN** PIPELINE BUOY PIPELINE BUOY ANCHOR BUOY .=43.1 MLLW LL=44.1 MLLW LL=43.1 MLLW DREDGE PIPELINE DREGE STERN LL=47.1 MLLW 4 LL=43.1 MLLW DREDGE ANCHOR BUOY GULFPORT ENERGY, 6" NATURAL GAS PIPELINE CALCASIEU SHIP CHANNEL LOWER SHEET 13 CR_13_LWR_20221212_PR LOWER S _13_LWR_2 12 Decem 566,000 563,000 Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. VICINITY MAP z — **LEGEND** Vertical Datum: -16' and above NTRIP VRS RTK: 0.94 MLLW AVG Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73595 as of December 2013:

0.0' NAVD88 (OPUS 2013) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG Gage Reading: 3 Fluff Thickness (feet)* -16' to -21' CALM Sea Conditions: --- Federal Navigation Channel Cable Area **MV TECHE** -21' to -26' Vessel Name: — Federal Navigation Center Line Placement Area Shoalest Sounding** Distances on the Calcasieu River are shown at 1 mile intervals. Survey Type: CONDITION -26' to -33' Esri, HERE, Garmin (c) OpenSt the GIS user Channel Sounding Frequency***: LOW The location of navigation aids are base on and provided by the U.S. Coast Guard Upper Channel [__] Anchorage Area As-built Pipeline/Cable Beacon, General -33' to -39' and USACE survey crews. -39' to -41' ∅ Obstruction Point Unconfirmed Pipeline/Cable 2022 Aerial Photography data source: PAR LLC Red Navigation Buoy 40 41 42 43 44 45 46 47 48 49 Sheet -41' to -43' Reference is N.O.A.A. Navigation Chart No. 11339. Wrecks-Submerged — Project Depth Contour Reference -43' and below Green Navigation Buoy 1,200 400 * Difference between high and low frequency elevations where greater than 1.0'. Number 13 **of** 53 ** Shoalest Sounding per Quarter per Reach. *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz)

Revison Number: 4.2-20200420

survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer