



LEGEND

--- Federal Navigation Channel	○ Cable Area	3 Fluff Thickness (feet)*	-16' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	-16' to -21'
— As-built Pipeline/Cable	⊗ Anchorage Area	★ Beacon, General	-21' to -26'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	-26' to -33'
— Project Depth Contour	⊗ Wrecks-Submerged	◆ Green Navigation Buoy	-33' to -39'
			-39' to -41'
			-41' to -43'
			-43' and below

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW).
Datum Relationships for gage 73595 as of December 2013:
0.0' NAVD83 (OPUS 2013) = 0.9' MLLW = 1.9' M.L.G. or 0.0' MLLW = 1.0' M.L.G.

Distances on the Calcasieu River are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.

2022 Aerial Photography data source: PAR LLC
Reference is N.O.A. Navigation Chart No. 11339.

* Difference between high and low frequency elevations where greater than 1.0'.
** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Gage Reading: DM86 VRS RTK: 1.55 MLLW AVG
Sea Conditions: CALM
Vessel Name: MV TECHE
Survey Type: CONDITION
Sounding Frequency***: LOW



DISCLAIMER: The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that the data are not warranted for any particular purpose, expressed or implied, or for any particular purpose of the recipient. The user is responsible for the results and accuracy of the data for their own use. The user shall be held responsible for any liability whatsoever to any person by reason of any use of the data for any purpose other than that for which they were prepared. The recipient may not transfer these data to others without obtaining the permission of the Army Corps of Engineers. The recipient may not transfer these data to others without obtaining the permission of the Army Corps of Engineers. The recipient may not transfer these data to others without obtaining the permission of the Army Corps of Engineers. The recipient may not transfer these data to others without obtaining the permission of the Army Corps of Engineers.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT	
Submitted: SP-JS	Surveyed By: SP-JS
Recommended: JH	Plotted By: JH
Approved: JH	Checked By: JH

**CALCASIEU SHIP CHANNEL
LOWER SHEET 13
CR_13_LWR_20231102_CS
02 November 2023**

**Sheet Reference Number
13 of 53**