

DISCLAIMER
Access Constraints: The United States Government furnishes these data and information with the understanding that recipient fully agrees not to represent these data to anyone as other than the data furnished. The United States shall be held harmless from any liability arising from any misrepresentation made thereof. These data belong to the Government. Therefore the recipient fully agrees not to represent these data to anyone as other than the data furnished by the Government. The United States shall be held harmless from any liability arising from any misrepresentation made thereof. These data belong to the Government. Therefore the recipient fully agrees not to represent these data to anyone as other than the data furnished by the Government.

Distribution Liability: The data represents the results of data collection and analysis performed by the U.S. Army Corps of Engineers activity and indicates the general existing conditions. As such, it is only valid for its intended use, content, time and accuracy of the survey. The U.S. Army Corps of Engineers is not liable for any of any of the application of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change over time due to environmental processes occurring between the activity and natural shoaling and scouring processes. The U. S. Army Corps of Engineers assumes no responsibility for changes in the hydrographical conditions which develop after the date of publication. This data is intended for U. S. Army Corps of Engineers' internal use. Present or intended use by any party is at

DISCLAIMER
Access Constraints: The United States Government furnishes these data and information with the understanding that recipient fully agrees not to represent these data to anyone as other than the data furnished. The United States shall be held harmless from any liability arising from any misrepresentation made thereof. These data belong to the Government. Therefore the recipient fully agrees not to represent these data to anyone as other than the data furnished by the Government. The United States shall be held harmless from any liability arising from any misrepresentation made thereof. These data belong to the Government. Therefore the recipient fully agrees not to represent these data to anyone as other than the data furnished by the Government.

US Army Corps of Engineers
District: CEMVN

U.S. ARMY CORPRS OF ENGINEERS
NEW ORLEANS DISTRICT

Submitted:	Surveyed By: SP, JS	
	Plotted By: JH	
Recommended: Chief, Survey Section		
Approved: Chief, Waterways Maintenance Section	Checked By: JH	

CALCASIEU SHIP CHANNEL
LOWER SHEET 13
CR_13_LWR_20250127_CS
27 January 2025

Sheet Reference Number
13 **of** 53

Revison Number:
4.2-20200420

VICINITY MAP



LEGEND

- Federal Navigation Channel
- Federal Navigation Center Line
- As-built Pipeline/Cable
- Unconfirmed Pipeline/Cable
- Project Depth Contour
- Cable Area
- Placement Area
- Anchorage Area
- Obstruction Point
- Wrecks-Submerged
- 3 Fluff Thickness (feet)*
- Shoalest Sounding**
- Beacon, General
- Red Navigation Buoy
- Green Navigation Buoy
- -16' and above
- -16' to -21'
- -21' to -26'
- -26' to -33'
- -33' to -39'
- -39' to -41'
- -41' to -43'
- -43' and below

Gage Reading:	DM 86 VRN: 0.4 MLLW AVG
Sea Conditions:	CALM
Vessel Name:	MV TECHE
Survey Type:	CONDITION
Sounding Frequency***:	LOW

Feet
0 400 800 1,200 1,600

NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73595 as of December 2013:
0.0' NAVD88 (OPUS 2013) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG

Distances on the Calcasieu River are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.

2022 Aerial Photography data source: PAR LLC

Reference is N.O.A.A. Navigation Chart No. 11339.

* Difference between high and low frequency elevations where greater than 1.0'.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.