


LEGEND			
--- Federal Navigation Channel	○ Cable Area	3 Fluff Thickness (feet)*	-16' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	-16' to -21'
— As-built Pipeline/Cable	⊗ Anchorage Area	☆ Beacon, General	-21' to -26'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	-26' to -33'
— Project Depth Contour	⊗ Wrecks-Submerged	◆ Green Navigation Buoy	-33' to -39'
			-39' to -41'
			-41' to -43'
			-43' and below



Gage Reading: =HACKBERRY: 1.0 MLLW
 Sea Conditions: CALM
 Vessel Name: M/V LAFOURCHE
 Survey Type: CONDITION
 Sounding Frequency***: LOW

NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW).
 Datum Relationships for gage 73600 as of December 2013:
 0.0' NAVD88 (OPUS 2010) = 1.0' MLLW = 2.0' MLG or 0.0' MLLW = 1.0' MLG
 Distances on the Calcasieu River are shown at 1 mile intervals.
 The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.
 2015 Aerial Photography data source: NAIP
 Reference is N.O.A. Navigation Chart No. 11339.
 * Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



DISCLAIMER:
 Access Conditions: The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that the data are provided for informational purposes only and are not to be used for any purpose other than that for which they were provided. The user is responsible for the results of any use of the data. The Corps of Engineers does not warrant the accuracy, reliability, or availability for any particular purpose of the data. The Corps of Engineers does not accept any responsibility for changes in the data or for the results of any use of the data. The Corps of Engineers does not accept any responsibility for changes in the data or for the results of any use of the data.
 Distribution Liability: The data represent the results of data collection for a specific US Army Corps of Engineers project and are only valid for its intended use, control, time and accuracy specifications. The user is responsible for the results of any use of the data. The Corps of Engineers does not warrant the accuracy, reliability, or availability for any particular purpose of the data. The Corps of Engineers does not accept any responsibility for changes in the data or for the results of any use of the data.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT		
Submitted:	Surveyed By:	JH/PS
Recommended:	Plotted By:	BD
Approved:	Chief, Survey Section	
	Chief, Waterways Maintenance Section	AC

**CALCASIEU SHIP CHANNEL
 LOWER SHEET 15
 CR_15_LWR_20190124_CS
 24 January 2019**

**Sheet Reference Number
 15 of 53**