


**DISCLAIMER**  
 The information depicted on this map represents the results of a survey conducted by the United States Government. The user of this information is advised that the United States Government does not warrant, either expressly or impliedly, the accuracy, reliability, or availability of this information for any purpose other than that for which it was prepared. The user is responsible for the results of any use of this information. The user is advised that the United States Government does not assume any liability for damages, including but not limited to, consequential damages, arising from the use of this information. The user is advised that the United States Government does not assume any liability for damages, including but not limited to, consequential damages, arising from the use of this information. The user is advised that the United States Government does not assume any liability for damages, including but not limited to, consequential damages, arising from the use of this information.


Submitted:	Surveyed By:	JDH/ADAMS
Recommended:	Plotted By:	BD
Checked:	Chart, Survey Section	
Approved:	Chief, Waterways Maintenance Section	AC

**CALCASIEU SHIP CHANNEL  
 LOWER SHEET 15  
 CR\_15\_LWR\_20200616\_CS\_POSTSTORM  
 16 June 2020**

**Sheet Reference Number  
 15 of 53**



LEGEND	
--- Federal Navigation Channel	● Cable Area
— Federal Navigation Center Line	□ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point
— Project Depth Contour	⊗ Wrecks-Submerged
3 Fluff Thickness (feet)*	★ Beacon, General
● Shoalest Sounding**	◆ Red Navigation Buoy
★ Beacon, General	◆ Green Navigation Buoy



**NOTES:**  
 Horizontal Coordinate System:  
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.  
 Vertical Datum:  
 Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW).  
 Datum Relationships for gage 73600 as of December 2013:  
 0.0' NAVD88 (OPUS 2010) = 1.0' MLLW = 2.0' MLG or 0.0' MLLW = 1.0' MLG  
 Distances on the Calcasieu River are shown at 1 mile intervals.  
 The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.  
 2015 Aerial Photography data source: NAIP  
 Reference is N.O.A.A. Navigation Chart No. 11339.  
 \* Difference between high and low frequency elevations where greater than 1.0'.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.