



LEGEND

--- Federal Navigation Channel	○ Cable Area	3 Fluff Thickness (feet)*	-16' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	-16' to -21'
— As-built Pipeline/Cable	⊗ Anchorage Area	☆ Beacon, General	-21' to -26'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	-26' to -33'
— Project Depth Contour	⚓ Wrecks-Submerged	◇ Green Navigation Buoy	-33' to -39'
			-39' to -41'
			-41' to -43'
			-43' and below

Gage Reading: HACKBERRY VRN: 0.2 MLLW AVG
 Sea Conditions: CALM
 Vessel Name: MV TECHE
 Survey Type: CONDITION
 Sounding Frequency***: LOW

NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73600 as of December 2013:
 0.0' NAVD88 (OPUS 2010) = 1.0' MLLW = 2.0' MLG or 0.0' MLLW = 1.0' MLG
 Distances on the Calcasieu River are shown at 1 mile intervals.
 The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.
 2022 Aerial Photography data source: PAR LLC
 Reference is N.O.A. Navigation Chart No. 11339.
 * Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

US Army Corps of Engineers
 District: CEMVN

DISCLAIMERS:
 Access: Complainants: The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that they are for informational purposes only. It is only valid for the intended use, content, time and accuracy specifications. The user is responsible for the results obtained. Appropriation of the data for other than the intended purpose.
 Data: Constants: Hydrographic survey data is subject to change rapidly due to several factors including, but not limited to, changing hydrographic conditions, navigational conditions, and changes in the hydrographic conditions which develop after the date of the survey. The recipient may not transfer these data to other users without the written consent of the United States Government. The recipient may not transfer the information depicted on this map to other users without the written consent of the United States Government. The recipient may not transfer the information to other users without the written consent of the United States Government. The recipient may not transfer the information to other users without the written consent of the United States Government. The recipient may not transfer the information to other users without the written consent of the United States Government.

U.S. ARMY CORPS OF ENGINEERS
 NEW ORLEANS DISTRICT

Submitted:	Surveyed By:	Plotted By:	Checked By:
	SP-JS	JH	JH
Recommended:	Chart, Survey Section		
Approved:	Chart, Waterways Maintenance Section		

CALCASIEU SHIP CHANNEL
LOWER SHEET 15
 CR_15_LWR_20250127_CS
 27 January 2025

Sheet Reference Number
15 of 53

Revision Number:
 4-2-2010/04/20