U.S. ARMY **CORPS OF ENGINEERS** 533,000 536,000 US Army Corps of Engineers District: CEMVN DISPOSAL AREA CALCASIEU CHANNEL LL=44.9 MLLW 4 LL=45.9 MLLW 4 LL=45.9 MLLW LL=45.9 MLLW LL=45.9 MLLW 4 CALCASIEU SHIP CHANNEL LOWER SHEET 17 CR_17_LWR_20240904_CS LOWER S _17_LWR_2 04 Septem 2,644,000 536,000 533,000 NOTES: Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane VICINITY MAP Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Vertical Datum: -16' and above DM 72 VRN: 2.10 MLLW AVG Gage Reading: Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73615 as of December 2013: 0.0' NAVD88 (2009.55) = 1.1' MLLW = 2.1' MLG or 0.0' MLLW = 1.0' MLG 3 Fluff Thickness (feet)* CHOP -16' to -21' Sea Conditions: --- Federal Navigation Channel Cable Area **MV TECHE** Vessel Name: -21' to -26' — Federal Navigation Center Line Placement Area Shoalest Sounding** Distances on the Calcasieu River are shown at 1 mile intervals. CONDITION Survey Type: -26' to -33' Esri, HERE Garmin, (c) OpenStrocontributors Sounding Frequency***: LOW --- Anchorage Area The location of navigation aids are base on and provided by the U.S. Coast Guard **Upper Channel** -33' to -39' As-built Pipeline/Cable Beacon, General and USACE survey crews. -39' to -41' ∅ Obstruction Point Unconfirmed Pipeline/Cable 2022 Aerial Photography data source: PAR LLC 40 41 42 43 44 45 46 47 48 49 Red Navigation Buoy Sheet -41' to -43' Reference is N.O.A.A. Navigation Chart No. 11339. Wrecks-Submerged — Project Depth Contour Reference -43' and below Green Navigation Buoy 400 800 1,200 * Difference between high and low frequency elevations where greater than 1.0'. Number 17 **of** 53 ** Shoalest Sounding per Quarter per Reach. *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) Bar Charnel ERE, Garmin, (c) OpenStreet Wiles contributors, and the GIS user community survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Revison Number: material. Low frequency accuracies may vary depending on channel conditions and fathometer 4.2-20200420