



DISCLAIMER: The United States Government furnishes these data and the recipient, accepts and uses them with the expressed understanding that the US Government makes no warranties, expressed, or implied concerning the accuracy, completeness, timeliness, utility, or reliability of any information supplied by the United States Government. The United States Government shall not be liable whatsoever to any person by reason of any use made therefrom. These data belong to the Government. Therefore the recipient fully agrees not to represent these data to anyone as other than Government provided data. The recipient may not transfer these data to others without also transferring this Disclaimer.

The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general condition existing at that time.

U.S. ARMY CORPS OF ENGINEERS	
Submitted: _____	Reviewed By: SP/JS _____
Recommended: Chief, Survey Section _____	Printed By: BD _____
Approved: Chief, Watersways Maintenance Section _____	Checked By: AOJ/H _____

**Sheet
Reference
Number**
18 **of** 53

NOTES: 524,000

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW)
Datum (Relationships for year 73615 as of December 2013:
0.0' NAVD83 (2009.55) = 1.1' MLLW = 2.1' MLG or 0.0' MLLW = 1.0' MLG

Distances on the Calcasieu River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard
and USACE survey crews.

2022 Aerial Photography data source: PAR LLC

Reference is N.O.A.A. Navigation Chart No. 11339.

* Difference between high and low frequency elevations where greater than 1.0'.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding
location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz)
survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bot-
tom material. Low frequency accuracies may vary depending on channel conditions and bathymetric
settings.