U.S. ARMY CORPS OF ENGINEERS 521,000 524,000 2,647,000 518,000 US Army Corps of Engineers District: CEMVN LONG POINT (DM 72) -73615 (0.0' NAVD88 = 1.1' MLLW = 2.1' MLG) Long Point Lake CALCASIEU SHIP CHANN LOWER SHEET 19 R_19_LWR_2015043 30 April 2015 521,000 524,000 518,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** -15' and above Gage Reading: DM 72: 3.00 MLG -15' to -20' cALM Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 73615 as of December 2013: --- Federal Navigation Channel Sea Conditions: Cable Area Borrow Area OB-167 -20' to -25' Vessel Name: 0.0' NAVD88 (2009.55) = 1.1' MLLW = 2.1' MLG or 0.0' MLLW = 1.0' MLG 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 Shoalest Sounding** Survey Type: CONDITION -25' to -32' Distances on the Calcasieu River are shown at 1 mile intervals. Esri, HERE DeLorme Mapmy India, © OpenStreetMap contributor Charles Community Sounding Frequency***: LOW **Upper Channel** -32' to -38' As-built Pipeline/Cable Anchorage Area Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews. -38' to -40' ∅ Obstruction Point ---- Unconfirmed Pipeline/Cable Red Navigation Buoy Sheet -40' to -42' 2010 Aerial Photography data source: NAIP Wrecks-Submerged — Project Depth Contour Reference -42' and below Reference is N.O.A.A. Navigation Chart No. 11339. Green Navigation Buoy 1,200 Number 400 ** Shoalest Sounding per Quarter per Reach. 19 **of** 53 *** High frequency (200 kHz) survey data represents the first signal return at a sounding 27 28 29 30 31 32 33 34 location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Bar Charriet ERE, DeLorme, MapmyIndia, © Oper contributors, and the GIS user community Revison Number: 3.6.1-20140429 material. Low frequency accuracies may vary depending on channel conditions and fathometer