U.S. ARMY **CORPS OF ENGINEERS** 521,000 518,000 524,000 2,647,000 HAH US Army Corps of Engineers DISPOSAL AREA "F" District: CEMVN LONG POINT (DM 72) -73615 (0.0' NAVD88 = 1.1' MLLW = 2.1' MLG) ⊗ LIGHT 72 1 L=45.0 MLLW__ 2LL=44.0 MLLW LL=44.0 MLLW C43/3ANNEL L=44.0 MLLW LL=44.0 MLLW 4 SHEET LOWER S _19_LWR_3 03 Decem 521,000 NOTES: 518,000 524,000 CALCASIEU Horizontal Coordinate System: VICINITY MAP North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Vertical Datum: -16' and above DM 72 VRN: 0.05 MLLW AVG Gage Reading: Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). 3 Fluff Thickness (feet)* CHOPPY Datum Relationships for gage 73615 as of December 2013: -16' to -21' Sea Conditions: --- Federal Navigation Channel Cable Area 0.0' NAVD88 (2009.55) = 1.1' MLLW = 2.1' MLG or 0.0' MLLW = 1.0' MLG **MV TECHE** -21' to -26' Vessel Name: 11 12 13 14 15 16 17 18 19 20 — Federal Navigation Center Line Placement Area Shoalest Sounding** Distances on the Calcasieu River are shown at 1 mile intervals. CONDITION Survey Type: -26' to -33' Esri, HERE Garmin (c) OpenStr the GIS user Channel Sounding Frequency***: LOW The location of navigation aids are base on and provided by the U.S. Coast Guard **Upper Channel** [__] Anchorage Area As-built Pipeline/Cable -33' to -39' Beacon, General and USACE survey crews. -39' to -41' ∅ Obstruction Point ---- Unconfirmed Pipeline/Cable 2022 Aerial Photography data source: PAR LLC Red Navigation Buoy Sheet -41' to -43' Reference is N.O.A.A. Navigation Chart No. 11339. Wrecks-Submerged — Project Depth Contour Reference -43' and below Green Navigation Buoy 400 1,200 * Difference between high and low frequency elevations where greater than 1.0'. Number ** Shoalest Sounding per Quarter per Reach. 19 **of** 27 28 29 30 31 32 33 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) Revison Number: 4.2-20200420 survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer