


**DISCLAIMER:** The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that the data is provided for informational purposes only. It is not to be used for any purpose other than that for which it was provided. The user is responsible for the accuracy, completeness, and timeliness of the data. The user is responsible for the accuracy, completeness, and timeliness of the data. The user is responsible for the accuracy, completeness, and timeliness of the data.

**DISCLAIMER:** The information depicted on this map represents the results of a hydrographic survey conducted by the United States Army Corps of Engineers. The data is provided for informational purposes only. It is not to be used for any purpose other than that for which it was provided. The user is responsible for the accuracy, completeness, and timeliness of the data.


Submitted:	SPSR	Plotted By:	BD	Checked By:	AD/JH
Recommended:	Chief, Survey Section				
Approved:	Chief, Waterways Maintenance Section				

**CALCASIEU SHIP CHANNEL**  
**GAP SHEET 27**  
**CR\_27\_GAP\_20221206\_CS**  
**06 December 2022**



**LEGEND**

--- Federal Navigation Channel	● Cable Area	3 Fluff Thickness (feet)*	■ -16' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	■ -21' to -26'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -26' to -33'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	■ -33' to -39'
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	■ -39' to -41'
			■ -41' to -43'
			■ -43' and below



**NOTES:**  
 Horizontal Coordinate System:  
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.  
 Vertical Datum:  
 Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW).  
 Datum Relationships for gage 73650 as of December 2013:  
 0.0' NAVD83 (2009.55) = 1.3' MLLW = 2.3' MLG or 0.0' MLLW = 1.0' MLG  
 Distances on the Calcasieu River are shown at 1 mile intervals.  
 The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.  
 2022 Aerial Photography data source: PAR LLC  
 Reference is N.O.A. Navigation Chart No. 11339.  
 \* Difference between high and low frequency elevations where greater than 1.0'.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

**Sheet Reference Number**  
**27 of 53**