U.S. ARMY CORPS OF ENGINEERS 464,000 461,000 US Army Corps of Engineers District: CEMVN LL=58.4 MLLW 4 LL=51.4 MLLW LL=54.4 MLLW 5 LL=53.4 MLLW 5 CRANE BARGES CALCASIEU SHIP CHANNEL GAP SHEET 27 CR\_27\_GAP\_20240221\_CS 461,000 NOTES: 467,000 464,000 Horizontal Coordinate System: VICINITY MAP North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Vertical Datum: -16' and above CAMERON: 0.57 MLLW Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73650 as of December 2013: 0.0' NAVD88 (2009.55) = 1.3' MLLW = 2.3' MLG or 0.0' MLLW = 1.0' MLG Gage Reading: 3 Fluff Thickness (feet)\* -16' to -21' CHOPPY --- Federal Navigation Channel Cable Area Sea Conditions: M/V TECHE -21' to -26' Vessel Name: 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 Shoalest Sounding\*\* Distances on the Calcasieu River are shown at 1 mile intervals. CONDITION Survey Type: -26' to -33' Esri, HERE Garmin, (c) Lower Channel Sounding Frequency\*\*\*: LOW **Upper Channel** The location of navigation aids are base on and provided by the U.S. Coast Guard As-built Pipeline/Cable -33' to -39' Anchorage Area Beacon, General and USACE survey crews. -39' to -41' ∅ Obstruction Point --- Unconfirmed Pipeline/Cable 2022 Aerial Photography data source: PAR LLC Red Navigation Buoy Sheet -41' to -43' Reference is N.O.A.A. Navigation Chart No. 11339. — Project Depth Contour Wrecks-Submerged Reference -43' and below **Green Navigation Buoy** 800 1,200 \* Difference between high and low frequency elevations where greater than 1.0'. Number 400 \*\* Shoalest Sounding per Quarter per Reach. 27 **of** 53 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Revison Number: material. Low frequency accuracies may vary depending on channel conditions and fathometer 4.2-20200420