



LEGEND	
--- Federal Navigation Channel	● Cable Area
— Federal Navigation Center Line	□ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point
— Project Depth Contour	⚓ Wrecks-Submerged
3 Fluff Thickness (feet)*	★ Beacon, General
● Shoalest Sounding**	◆ Red Navigation Buoy
● Green Navigation Buoy	

Gage Reading: CAMERON VRN: 1.54 MLLW AVG.  
 Sea Conditions: CHOPPY  
 Vessel Name: MV TECHE  
 Survey Type: CONDITION  
 Sounding Frequency\*\*\*: LOW

Vertical Datum:  
 Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW).  
 Datum Relationships for gage 73650 as of December 2013:  
 0.0' NAVD88 (2009.55) = 1.3' MLLW = 2.3' MLG or 0.0' MLLW = 1.0' MLG

Distances on the Calcasieu River are shown at 1 mile intervals.  
 The location of navigation aids are based on and provided by the U.S. Coast Guard and USACE survey crews.

2015 Aerial Photography data source: NAIP  
 Reference is N.O.A.A. Navigation Chart No. 11339.

\* Difference between high and low frequency elevations where greater than 1.0'.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



**US Army Corps of Engineers District: CEMVN**

The information depicted on this map represents the results of a hydrographic survey conducted by the U.S. Army Corps of Engineers. The data was collected using a CHIRP echosounder and a GNSS receiver. The data was processed using the following parameters: Vertical Datum: MLLW; Horizontal Datum: NAD83; Sounding Frequency: 200 kHz. The data was collected on 19 July 2024. The information depicted on this map represents the results of a hydrographic survey conducted by the U.S. Army Corps of Engineers. The data was collected using a CHIRP echosounder and a GNSS receiver. The data was processed using the following parameters: Vertical Datum: MLLW; Horizontal Datum: NAD83; Sounding Frequency: 200 kHz. The data was collected on 19 July 2024.

Submitted:	Surveyed By: SP,JS
Recommended:	Plotted By: BD
Approved:	Checked By: ADU/JH

U.S. ARMY CORPS OF ENGINEERS  
 NEW ORLEANS DISTRICT

**CALCASIEU SHIP CHANNEL**  
**BAR SHEET 35**  
**CR\_35\_BAR\_20240719\_CS**  
**19 July 2024**

**Sheet Reference Number**  
**35 of 53**