



LEGEND

- Federal Navigation Channel
- Federal Navigation Center Line
- As-built Pipeline/Cable
- Unconfirmed Pipeline/Cable
- Project Depth Contour
- Cable Area
- Placement Area
- Anchorage Area
- Obstruction Point
- ✈ Wrecks-Submerged
- 3 Fluff Thickness (feet)**
- Shoalest Sounding**
- ★ Beacon, General
- ★ Red Navigation Buoy
- ◆ Green Navigation Buoy
- 15' and above
- 15' to -20'
- 20' to -25'
- 25' to -32'
- 32' to -38'
- 38' to -40'
- 40' to -42'
- 42' and below

Gage Reading: CAMERON: 2.5 MLG AVG
 Sea Conditions: 1-3' SEAS
 Vessel Name: MV TECHE
 Survey Type: CONDITION
 Sounding Frequency***: LOW

Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Low Gull Datum (MLG).
 Datum Relationships for page 73650 as of December 2013:
 0.0' NAVD88 (2009.55) = 1.3' MLLW = 2.3' MLG or 0.0' MLLW = 1.0' MLG

Distances on the Calcasieu River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard and USACE survey crews.

2015 Aerial Photography data source: NAIP
 Reference is N.O.A. Navigation Chart No. 11339.

* Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

US Army Corps of Engineers
 District: CEMVNV

Division: The United States Government furnishes this data for informational purposes only. It is not intended for use in any other manner. The user is responsible for the accuracy, reliability, and availability of the data for their intended purpose. The user is responsible for the accuracy, reliability, and availability of the data for their intended purpose. The user is responsible for the accuracy, reliability, and availability of the data for their intended purpose.

U.S. ARMY CORPS OF ENGINEERS
 NEW ORLEANS DISTRICT

Submitted: _____
 Recommended: _____
 Checked By: _____
 Approved: _____

CALCASIEU SHIP CHANNEL
 BAR SHEET 36
 CR_36_BARX_20160921
 21 September 2016

Sheet Reference Number
 36 of 53

Revision Number:
 15-9-20160000