




Compass rose showing North (N), South (S), East (E), and West (W).

Scale bar labeled "Feet" with markings at 0, 400, 800, 1,200, and 1,600.

NOTE: Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Data Relationships for gauge 73650 as of December 2013: 0.0' NAVD83 (2009.55) = 1.3' MLLW = 2.3' MGLG or 0.0' MLLW = 1.0' MGLG

Distances on the Calcasieu River are shown at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard and USACE survey crews.

Aerial Photography data source: BUMP 2026 (DOQQ 1998 in transparent green)

Reference is N.O.A.A. Navigation Chart No. 11339.

* Difference between high and low frequency elevations were greater than 1.0'.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (200 kHz) data normally penetrates through this "fluff" layer to depict elevations of consolidated material. Low frequency accuracies may vary depending on channel conditions and bathymetry.

**Sheet
Reference
Number**
49 **of** 53