U.S. ARMY CORPS OF ENGINEERS 632,000 2,674,000 US Army Corps of Engineers District: CEMVN LL=38.2 MLLW LL=37.2 MLLW LL=44.2 MLLW LL=44.2 MLLW CALCASIEU SHIP CHANNEL
CLOONEY ISLAND
CR\_52\_CLI\_20231025\_CS
25 October 2023 2,671,000 632,000 2,668,000 NOTES: Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. VICINITY MAP **LEGEND** -16' and above LAKE CHARLES: 1.83 MLLW AVG. Gage Reading: Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum Relationships for gage 73550 as of December 2013:

0.0' NAVD88 (OPUS 2010) = 0.6' MLLW = 1.6' MLG or 0.0' MLLW = 1.0' MLG 3 Fluff Thickness (feet)\* CALM -16' to -21' Cable Area Sea Conditions: --- Federal Navigation Channel M/V TECHE -21' to -26' Vessel Name: — Federal Navigation Center Line Placement Area Shoalest Sounding\*\* Distances on the Calcasieu River are shown at 1 mile intervals. CONDITION Survey Type: -26' to -33' Esri, HERE Garmin (c) OpenSt the GIS user Channel Sounding Frequency\*\*\*: LOW The location of navigation aids are base on and provided by the U.S. Coast Guard **Upper Channel** As-built Pipeline/Cable Anchorage Area Beacon, General -33' to -39' and USACE survey crews. -39' to -41' ∅ Obstruction Point ..... Unconfirmed Pipeline/Cable 2022 Aerial Photography data source: PAR LLC Red Navigation Buoy Sheet -41' to -43' Reference is N.O.A.A. Navigation Chart No. 11339. Wrecks-Submerged — Project Depth Contour Reference -43' and below Green Navigation Buoy 1,200 400 \* Difference between high and low frequency elevations where greater than 1.0'. Number 52 **of** 53 \*\* Shoalest Sounding per Quarter per Reach. \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Revison Number: 4.2-20200420 material. Low frequency accuracies may vary depending on channel conditions and fathometer