

US Army Corps of Engineers District: CEMVN


Distribution Liability: The data represents the results of data collection/processing for a specific US Army Corps of Engineers project. It is only valid for its intended use, content, time and accuracy specifications. The user is responsible for the results and accuracy of the data for other than its intended purpose. Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to changing hydrographic conditions which develop after the date of the survey. The user is responsible for the accuracy of the data for other than its intended purpose. The information depicted on this map represents the results of a survey conducted on the date of the survey. It is not intended to represent the general condition existing at that time.

| | | | |
|--------------|--------------------------------------|----------------|----------------|
| Submitted: | Surveyed By: SP,SR | Plotted By: AO | Checked By: AO |
| Recommended: | Chart, Survey Section | | |
| Approved: | Chart, Waterways Maintenance Section | | |

**CALCASIEU SHIP CHANNEL
COON ISLAND
CR_53_CNI_20191121_CS
21 November 2019**

**Sheet Reference Number
53 of 53**

Revision Number: 4/8-2019/10/2



| LEGEND | | |
|----------------------------------|---------------------|---------------------------|
| --- Federal Navigation Channel | ○ Cable Area | 3 Fluff Thickness (feet)* |
| — Federal Navigation Center Line | □ Placement Area | ● Shoalest Sounding** |
| — As-built Pipeline/Cable | ⊗ Anchorage Area | ☆ Beacon, General |
| Unconfirmed Pipeline/Cable | ⊗ Obstruction Point | ◆ Red Navigation Buoy |
| — Project Depth Contour | ⊗ Wrecks-Submerged | ◆ Green Navigation Buoy |

Gage Reading: DM 114: 1.4 MLLW
 Sea Conditions: CALM
 Vessel Name: OB-167
 Survey Type: CONDITION, VRS
 Sounding Frequency***: LOW

Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW).
 Datum Relationships for gage 73550 as of December 2013:
 0.0' NAVD83 (OPUS 2010) = 0.6' MLLW = 1.6' MLG or 0.0' MLLW = 1.0' MLG

Distances on the Calcasieu River are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.

2015 Aerial Photography data source: NAIP
 Reference is N.O.A.A. Navigation Chart No. 11339.

* Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Revision Number: 4/8-2019/10/2