U.S. ARMY CORPS OF ENGINEERS 3,001,000 of Engineers District: CEMVN Vermillion Bay 234°48'37.7" 234°23'34.1",1.45'52°452 BASELINE AND U. S. R/W FRESHWATER BAYOU
UPPER CHANNEL
-B_03_UPR_20210413_C 13 April 2021 3,004,000 458,000 3,001,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane z dod Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Gage Reading: LB LOCK EAST: 4.1 MLG AVG. Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 76592 / 76593 as of August 2011: 0.0' NAVD88 (2006.81) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG WINDY/CHOPPY -12' and above --- Federal Navigation Channel Sea Conditions: Cable Area Borrow Area -12' and below OB-189 Vessel Name: — Federal Navigation Center Line Placement Area Shoalest Sounding** CONDITION Survey Type: Distances on the Freshwater Bayou are shown at 1 mile intervals. Sounding Frequency***: HIGH Anchorage Area As-built Pipeline/Cable Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews. ∅ Obstruction Point ---- Unconfirmed Pipeline/Cable Red Navigation Buoy Sheet 2017 Aerial Photography data source: NAIP — Project Depth Contour Wrecks-Submerged Reference Reference is N.O.A.A. Navigation Chart No. 11350. Green Navigation Buoy Number ** Shoalest Sounding per Quarter per Reach. 3 **of** 19 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Esri, HERE, Garmin, (c) OpenStreetM material. Low frequency accuracies may vary depending on channel conditions and fathometer Revison Number: contributors, and the GIS user

4.1-20191105