U.S. ARMY CORPS OF ENGINEERS 3,001,000 of Engineers District: CEMVN Vermillion Bay 234°48'31.5" 234°48'37.7" 734°23'34.1", 1.75'52°452 BASELINE AND U. S. R/W FRESHWATER BAYOU
UPPER CHANNEL
-B\_03\_UPR\_2022022\_C\$
22 February 2022 3,004,000 458,000 3,001,000 NOTES: VICINITY MAP Horizontal Coordinate System: Z ------North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** LB LOCK EAST: 3.4 MLG AVG Gage Reading: Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 76592 / 76593 as of August 2011: 0.0' NAVD88 (2006.81) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG Sea Conditions: CHOP -12' and above --- Federal Navigation Channel Cable Area Borrow Area OB-169 \_\_\_\_\_ -12' and below Vessel Name: — Federal Navigation Center Line Placement Area Shoalest Sounding\*\* CONDITION Survey Type: Distances on the Freshwater Bayou are shown at 1 mile intervals. Sounding Frequency\*\*\*: LOW Anchorage Area As-built Pipeline/Cable Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews. ∅ Obstruction Point ···· Unconfirmed Pipeline/Cable Red Navigation Buoy Sheet

— Project Depth Contour

Esri, HERE, Garmin, (c) OpenStreetM

contributors, and the GIS user commu

Wrecks-Submerged

Green Navigation Buoy

Distances on the Freshwater Bayou are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.

2017 Aerial Photography data source: NAIP

Reference is N.O.A.A. Navigation Chart No. 11350.

\*\* Shoalest Sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Reference

Number

Revison Number:

4.2-20200420

**of** 19