U.S. ARMY CORPS OF ENGINEERS 440,000 443,000 US Army Corps of Engineers District: CEMVN FRESHWATER BAYOU UPPER CHANNEL FB_06_UPR_20150609 09 June 2,989,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. z ~~ Vertical Datum:

CALM

OB-167

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).
Datum Relationships for gage 76592 / 76593 as of August 2011:
0.0' NAVD88 (2006.81) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG <u>LEGEND</u> Gage Reading: Sea Conditions: -12' and above --- Federal Navigation Channel Cable Area Borrow Area -12' and below Vessel Name: Shoalest Sounding** — Federal Navigation Center Line Placement Area Survey Type: Distances on the Freshwater Bayou are shown at 1 mile intervals. Sounding Frequency***: LOW As-built Pipeline/Cable [___] Anchorage Area Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews. ∅ Obstruction Point ---- Unconfirmed Pipeline/Cable Red Navigation Buoy Sheet 2010 Aerial Photography data source: NAIP — Project Depth Contour Wrecks-Submerged Reference Reference is N.O.A.A. Navigation Chart No. 11350. Green Navigation Buoy Number ** Shoalest Sounding per Quarter per Reach. 6 **of** 19 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer Esri, HERE, DeLorme, MapmyIndia, © contributors, and the GIS user commu Revison Number: 3.8.0-20150202