



**LEGEND**

--- Federal Navigation Channel

— Federal Navigation Center Line

— As-built Pipeline/Cable

..... Unconfirmed Pipeline/Cable

— Project Depth Contour

○ Cable Area

□ Placement Area

□ Anchorage Area

⊗ Obstruction Point

✈ Wrecks-Submerged

□ Borrow Area

● Shoalest Sounding\*\*

★ Beacon, General

◆ Red Navigation Buoy

◇ Green Navigation Buoy

■ -12' and above

□ -12' and below

Gage Reading: LBL WESTGAGE VRN: 3.41 MLG AVG

Sea Conditions: CHOPPY

Vessel Name: OB-189

Survey Type: CONDITION

Sounding Frequency\*\*\*: HIGH

**NOTES:**

Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane  
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).  
Datum Relationships for gage 76592 / 76593 as of August 2011:  
0.0' NAVD83 (2006.81) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG

Distances on the Freshwater Bayou are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.

2021 Aerial Photography data source: NAIP (1998 DOQQ imagery in green)

Reference is N.O.A.A. Navigation Chart No. 11350.

\*\* Shoalest Sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT			
Submitted:	Surveyed By: SPJS	Plotted By: BD	Checked By: AOJH
Recommended:	Chief, Survey Section	Chief, Waterways Maintenance Section	
Approved:			

**FRESHWATER BAYOU  
LOWER CHANNEL**

**FB\_08\_LWR\_20250603\_CS**

**03 June 2025**

**Sheet  
Reference  
Number**

**8 of 19**