U.S. ARMY CORPS OF ENGINEERS 2,989,000 419,000 of Engineers District: CEMVN 197°43'57.9" FRESHWATER BAYOU
LOWER CHANNEL

B_09_LWR_20240626_C\$

26 June 2024 425,000 422,000 419,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. Z ------**LEGEND** Gage Reading: LB LOCK EAST: 3.20 MLG AVG Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).

Datum Relationships for gage 76592 / 76593 as of August 2011:

0.0' NAVD88 (2006.81) = 0.9' MLLW = 1.9' MLG or 0.0' MLLW = 1.0' MLG Sea Conditions: 0-1FT --- Federal Navigation Channel Cable Area Borrow Area -12' and above OB169 Vessel Name: ____ -12' and below Shoalest Sounding** — Federal Navigation Center Line Placement Area CONDITION Survey Type: Distances on the Freshwater Bayou are shown at 1 mile intervals. Sounding Frequency***: LOW As-built Pipeline/Cable Anchorage Area Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews. ∅ Obstruction Point Unconfirmed Pipeline/Cable Red Navigation Buoy Sheet 2017 Aerial Photography data source: NAIP — Project Depth Contour Wrecks-Submerged Reference Reference is N.O.A.A. Navigation Chart No. 11350. Green Navigation Buoy 1,200 Number ** Shoalest Sounding per Quarter per Reach. 9 **of** 19 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer Revison Number:

4.2-20200420

contributors, and the GIS user commu