U.S. ARMY CORPS OF ENGINEERS 3,319,000 of Engineers District: CEMVN RIG MR CHARLIE FLOODWALL 27.27.20 TIDEWATER POINT 4404 BAYOU BOFILE OCODAND DOINT OTACOASTA! BATEMAN INTRACOASTAL 3,319,000 3,322,000 NOTES: **VICINITY MAP** Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** MORGAN CITY: 5.70 MLG AVG. Gage Reading: 0-1FT Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Sea Conditions: Borrow Area -- Federal Navigation Channel Cable Area Datum Relationships for Lower Atchafalaya River at Morgan City (03780) as of 2017: 0.0' NAVD88 (2009.55) = 1.89' MLG M/V VALENTOUR Vessel Name: -12' and above — Federal Navigation Center Line Placement Area Shoalest Sounding** CONDITION Survey Type: The location of navigation aids are base on and provided by the U.S. Coast Guard. ____ -12' and below Sounding Frequency***: HIGH As-built Pipeline/Cable Anchorage Area Beacon, General 2015 Aerial Photography data source: NAIP. 1998 DOQQ imagery shown in green from USGS. ∅ Obstruction Point Unconfirmed Pipeline/Cable Red Navigation Buoy Reference is N.O.A.A. Navigation Chart No. 11355. Sheet Wrecks-Submerged — Project Depth Contour ** Shoalest Sounding per Quarter per Reach. Reference Green Navigation Buoy 1,000 500 Number *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom 67 **of** 191 material. Low frequency accuracies may vary depending on channel conditions and fathometer Revison Number: 4.2-20200420