U.S. ARMY CORPS OF ENGINEERS 3,325,000 3,328,000 US Army Corps of Engineers District: CEMVN A HILL HARRING TO SEE THE SEE GULF INTRACOASTAL WATERWAY
MORGAN CITY DOCKS EAST
GW\_66\_BBW\_20160301
01 March 2016 3,325,000 3,328,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Gage Reading: MORGAN CITY: 5.20 MLG Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for Lower Atchafalaya River at Morgan City (03780) as of May 2014: Sea Conditions: CALM --- Federal Navigation Channel Cable Area Borrow Area OB-189 Vessel Name: -12' and above 0.0' NAVD88 (2009.55) = 2.05' MLG Shoalest Sounding\*\* — Federal Navigation Center Line Placement Area Survey Type: CONDITION \_\_\_\_\_ -12' and below The location of navigation aids are base on and provided by the U.S. Coast Guard. Sounding Frequency\*\*\*: HIGH As-built Pipeline/Cable Anchorage Area Beacon, General 2010 Aerial Photography data source: NAIP. 1998 DOQQ imagery shown in green from USGS. ∅ Obstruction Point ..... Unconfirmed Pipeline/Cable Red Navigation Buoy Reference is N.O.A.A. Navigation Chart No. 11355. Feet Sheet — Project Depth Contour Wrecks-Submerged \*\* Shoalest Sounding per Quarter per Reach. Reference Green Navigation Buoy 500 1,000 Number \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom 66 **of** 191 material. Low frequency accuracies may vary depending on channel conditions and fathometer Revison Number: 3.8.0-20150202 ontributors, and the GIS user community