



P.C. 6 1890+09.85
 X= 3,522,320.13
 Y= 221,166.34

CURVE 3 DATA
 Δ = 42° 18' 08.1996"
 D = 01° 09' 45.3966"
 T = 1906.6903'
 R = 4928.2024'
 L = 3638.5610'

SPD MI. 2.5
 X=3,517,470
 Y=227,124



DISCLAIMER
 The data represented on this map represents the results of a...
 Distribution Liability: The data represented on this map represents the results of a...
 The information depicted on this map represents the results of a...
 Internal Use: Product maintainers should not rely solely upon it.

Submitted:	Surveyed By: PM DR
Recommended:	Plotted By: BD
Approved:	Checked By: ADU/JH

U.S. ARMY CORPS OF ENGINEERS
 NEW ORLEANS DISTRICT
 Chart, Waterways Maintenance Section
 31 May 2023

**HOUMA NAVIGATION CANAL
 BAY CHANNEL
 HN_16_BAY_20230531_CS
 31 May 2023**

**Sheet Reference Number
 16 of 19**

LEGEND

--- Federal Navigation Channel	○ Cable Area	3 Fluff Thickness (feet)*	-8' and above
— Federal Navigation Center Line	▭ Placement Area	● Shoalest Sounding**	-8' to -10'
— As-built Pipeline/Cable	⊗ Anchorage Area	★ Beacon, General	-10' to -12'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	♦ Red Navigation Buoy	-12' to -16'
— Project Depth Contour	⚓ Wrecks-Submerged	♦ Green Navigation Buoy	-16' to -19'
			-19' and below

NOTES:

Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane
 Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW).
 Datum Relationships for 88455 as of September 2022:
 0.0' NAVD88 (OPUS 2019) = 0.40' MLLW (2012-2016) = 1.40' MLG

Distances on the Houma Nav. Canal are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.

2022 Aerial Photography data source: Optimal GEO, Inc. (1998 DOQQ Imagery in green)

Reference is N.O.A.A. Navigation Chart No. 11355.

* Difference between high and low frequency elevations where greater than 1.0'.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Gage Reading: VRS RTN: 1.46 MLLW AVG.
 Sea Conditions: CALM
 Vessel Name: OB-167
 Survey Type: CONDITION
 Sounding Frequency***: LO

Feet
 0 400 800 1,200 1,600 2,000

