U.S. ARMY CORPS OF ENGINEERS 3,322,000 **US Army Corps** of Engineers District: CEMVN TABLE OF COORDINATES APPROX LIMITS OF WORK POINT NO. 3320949.835 701715.189 3321101.868 701504.689 701174.795 3321639.985 700599.761 3322118.775 3322230.961 701181.825 3321961.024 701200.779 701292.296 3321811.849 701340.817 3321770.968 701399.342 3321806.013 3321042.882 701866.860 PORT ALLEN LOCK BATON ROUGE HARBOR PORT ALLEN LOCK FOREBAY LK_04_PAL_20250818_CS National Oceanic and Atmospheric Administration (NOAA) 3,319,000 3,322,000 701,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** BR: 14.0 NGVD29 Gage Reading: CALM Soundings are shown in feet and indicate depths below National Geodetic Verical Datum of 1929 --- Federal Navigation Channel Cable Area Borrow Area Sea Conditions: OB189 — Federal Navigation Center Line Placement Area Shoalest Sounding** Distances on the Mississippi River, above and below Head of Passes are shown CONDITION Survey Type: -8' and above Sounding Frequency***: HIGH As-built Pipeline/Cable Anchorage Area Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard.

∅ Obstruction Point

Wrecks-Submerged

Red Navigation Buoy

Green Navigation Buoy

-10' to -12'

-12' and below

200 300 400 500

..... Unconfirmed Pipeline/Cable

— Project Depth Contour

Esri, HERE, Garmin, (c) OpenStreetMap contributors, and

the GIS user community

	Surveyed By:	Plotted By: JH	Checked By: JH ——
U.S. ARMY COPRPS OF ENGINEERS NEW ORLEANS DISTRICT	Submitted:	Recommended: Chief, Survey Section	Approved: Chief, Waterways Maintenance Section

Sheet Reference Number of

2021 Aerial Photography data source: NAIP

** Shoalest Sounding per Quarter per Reach.

settings.

Reference is N.O.A.A. Navigation Chart No. 11370.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding

location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom

material. Low frequency accuracies may vary depending on channel conditions and fathometer

Revison Number: 5.25.04.03